

Exam : IBM 000-103

Title : AIX 6.1 Basic Operations

Version : Demo

1. An application owner wants to grant write permission to all users for all the files and directories in the application directory. Which of the following is the correct command?

- A. `chmod -R u+rw /application`
- B. `chmod -r u+rw /application`
- C. `chmod -R o+rw /application`
- D. `chmod -r o+rw /application`

Answer: C

2. The printer associated with the `hp5_queue` is down for maintenance. Which of the following commands will move the remaining print jobs from `hp5_queue` to the `hp7_queue`?

- A. `export $LPDEST=hp7_queue`
- B. `qmov -m hp7_queue -P hp5_queue`
- C. `lpmov -s hp5_queue -d hp7_queue`
- D. `redirect -q hp5_queue hp7_queue`

Answer: B

3. An operator needs to run a script which will write standard output and standard error to different files.

Which of the following commands will successfully perform this task?

- A. `myscript.ksh 1>/tmp/log/script.log 2>/tmp/log/script.err`
- B. `myscript.ksh $1>/tmp/log/script.log $2>/tmp/log/script.err`
- C. `myscript.ksh 1>/tmp/log/script.log 2>&1 /tmp/log/script/err`
- D. `myscript.ksh 2>&1 /tmp/log/script.log 2> /tmp/log/script.err`

Answer: A

4. An operator is trying to perform an immediate power down of an AIX LPAR using the `'shutdown -k'` command. The cursor has returned to the command prompt, but no shutdown activities are showing on the screen after more than one minute. Which of the following is the most likely cause of the problem?

- A. The `/etc/rc.shutdown` script is missing.
- B. The `bos.rte.control` fileset has become corrupted.
- C. The operator UID is not a member of the shutdown group.

D. The -k flag against the shutdown command only broadcast the shutdown message.

Answer: D

5. After making changes to the profile for an LPAR, the administrator asks the operator to bring the LPAR back up into a running state with the new changes. Which of the following is the correct way to do this?

- A. Shutdown and activate the partition profile
- B. Reboot the partition using the reboot command
- C. Reboot the partition using the 'shutdown -r' command
- D. Right click on the partition profile and select the 'apply changes' option

Answer: A

6. An operator has been asked if a system was rebooted. Which of the following commands should be used to determine if a reboot has occurred?

- A. The uname command.
- B. The uptime command.
- C. The shutdown last command.
- D. The /etc/rc.shutdown?command.

Answer: B

7. What is the correct command to display the current working directory?

- A. echo \$PWD
- B. echo \$pwd
- C. echo \$CWD
- D. echo \$cwd

Answer: A

8. What command will allow the operator to add the current working directory to the command search path?

- A. export PATH=pwd
- B. export PATH=\$PWD
- C. export PATH=\$PATH:pwd

D. export PATH=\$PATH:\$PWD

Answer: C

9. An operator needs to change from the /usr/bin to the /var/spool directory. Which of the following commands will accomplish this?

A. cd /var/spool

B. lcd /var/spool

C. cd /usr/bin /var/spool

D. lcd /usr/bin /var/spool

Answer: A

10. A user created a file name '.newfile' in the /save directory, but doesn't see the file when listing the directory contents. Which command will verify the file is in the directory?

A. ls -a /save

B. ls -e /save

C. lsdir -E /save

D. lsdir -A /save

Answer: A